



## 937415 RP300 CHROME (932805S+DN132D+RP300+4914Q3+1128C) 937415RP300

<b>Collection:</b> Blautherm	<b>Finish:</b> Chrome	<b>Code:</b> 94D308931
<b>Location:</b> Bath	<b>Category:</b> Shower	

### Technical characteristics

- Ceramic cartridge Ø35 mm.
- Diverter 2 ways without closure.
- Water saving system S2 through the handle opening in two fases.
- Flow rate at 3 bar (43 PSI): 12 l/min through hand shower outlet and 16 l/min through showerhead outlet.
- Thermal shock resistant and anti-Legionella chemical.
- Guarantee of 5 year for tapware and 3 years for accesories.
- Use pressure between 1-5 bar (14.5-72.5 PSI). Recomend pressure 3 bar (43 PSI).
- Resists static pressure equal to or less than 10 bar (145 PSI) and water hammer up to 25 bar.
- 3 bar (43 PSI) acoustic level less than 20 dB.
- Comfort benefits of fidelity, sensibility and constancy in temperature selection.
- Recommended temperature of use from 15°C to 55°C. Maximum use temperature 65°C. Maximum 1h at 90°C
- Chromed surface: 15 microns thick of nickel and 0.3 microns thick of chrome.
- Termostop Black system for maximum water temperature limitation.

### Tests

- Water tightness, flow rate, mechanical behavior under pressure, mechanical resistance, dimensional, acoustical and corrosion test according to european standards EN 817 and EN 248.

### Composition and spare parts

• Handle:	9400C2I-35 (94Z308991)
• Flow limiter:	LC1212 (AAZ310503)
• Cartridge:	35100-2 (AAZ300973)
• Cartridge nut cover:	9380-35 (AAZ311344)
• Cartridge nut:	TSC351 (250863)
• Diverter nut:	TSC354 (261914)
• Ceramic diverter:	4004 (AAZ300972)
• Seat:	AGM-2I (252816)
• Handle wheel:	9458LI (94Z308990)
• Check valve:	ARD15 (181680)
• Index:	DT1-CN (252825)
• Escutcheon + Eccentric:	1326 (210660)
• Escutcheon:	1323 (220749)
• Eccentric:	E1/23/4ST (160257)
• Hand shower:	4914Q3 (99Z306272)
• Screw seat:	T3/4 (160220)
• Shower support:	SD25 (AAZ306948)
• Joint kit:	BJDN132D (AAZ307894)

