



Sink mixer single lever chromed, extraible and swivel spout with magnet system  
**388801MA**

<b>Collection:</b> Kitchen	<b>Finish:</b> Chrome	<b>Code:</b> 38E303469
<b>Location:</b> Kitchen	<b>Category:</b> Kitchen sink	

## Technical characteristics

- Ceramic cartridge Ø25 mm.
- Flow rate at 3 bar: 9 l/min.
- Thermal shock resistant and anti-Legionella chemical.
- Guarantee of 5 year for tapware and 3 years for accesories.
- Use pressure between 1-5 bar. Recomendated pressure 3 bar.
- Resists static pressure equal to or less than 10 bar and water hammer up to 25 bar.
- 3 bar acoustic level less than 20 dB.
- Comfort benefits of fidelity, sensibility and constancy in temperature selection.
- Recomendated temperature for hot water: 55°C. Maximum temperature of use: 65°C up to 1 hour at 90°C.
- Chromed surface: 15 microns thick of nickel and 0.3 microns thick of chrome.

## Tests

- Water tightness, flow rate, mechanical behavior under pressure, mechanical resistance, dimensional, acoustical and corrosion test according to european standards EN 817 and EN 248.

## Composition and spare parts

- |                        |                        |
|------------------------|------------------------|
| • Handle:              | 380002I-25 (38Z303486) |
| • Cartridge nut cover: | 4970 (252843)          |
| • Cartridge nut:       | TSC256 (AAZ306246)     |
| • Cartidge:            | 25001-2 (AAZ306240)    |
| • Spout:               | F3868-88 (AAZ303941)   |
| • Hand shower:         | DC3888 (AAZ303942)     |
| • Support arm:         | BSC3888 (AAZ303944)    |
| • Base:                | 383001 (38Z305715)     |
| • Reinforcement base:  | BRF02 (AAZ304483)      |
| • Accesory bag:        | BAC38 (AAZ303940)      |
| • Felxible hose:       | 239R (AAZ301712)       |
| • Threaded tube:       | CRF320 (AAZ304358)     |

## Observations

