

Alexia, bath and shower mixer, chromed

3605S

Collection: Alexia
Finish: Cromo
Code: 36C300356
Location: Baño
Category: Bañera
Certification: N II D/A



Technical characteristics

- Certification AENOR.
- Ceramic cartridge Ø35 mm.
- Water saving system S2 through the handle opening in two fases.
- Flow rate at 3 bar (43 PSI): 20 l/min through bath outlet and 12 l/min through shower outlet.
- Thermal shock resistent and anti-Legionella chemical.
- Guarantee of 5 year for tapware and 3 years for accesories.
- Use pressure between 1-5 bar (14.5-72.5 PSI). Recomended pressure 3 bar (43 PSI).
- Resists static pressure equal to or less than 10 bar (145 PSI) and water hammer up to 25 bar.
- 3 bar (43 PSI) acoustic level less than 20 dB.
- Comfort benefits of fidelity, sensibility and constancy in temperature selection.
- Recommended temperature of use from 15°C to 55°C. Maximum use temperature 65°C. Maximum 1h at 90°C
- Chromed surface: 15 microns thick of nickel and 0.3 microns thick of chrome.
- Termostop Block system for maximum water temperature limitation.

Tests

- Water tightness, flow rate, mechanical behavior under pressure, mechanical resistance, dimensional, acoustical and corrosion test according to european standards EN 817 and EN 248.

Composition and spare parts

Handle:	3600-35 (36Z303036)
Index:	DT1-CN (252825)
Cartridge nut cover:	4980 (252834)
Cartridge nut:	TSC351 (250863)
Cartidge:	35100 (252204)
Aerator:	1534 (252879)
Diverter valve:	3675M (AAZ300860)
Check valve:	ARD15 (181680)
Seat:	AGM-2I (252816)
Screw seat:	T3/42C (AAZ300861)
Escutcheon:	1323 (220749)
Eccentric:	E1/23/4FAC (261913)
Escutcheon + Eccentric:	1326NF (AAZ302187)