



187402 **RP240** **CHROME**
 (1838S+DN132+IDH1/2+RP240+2876BT+1125C)
187402RP240

Collection: Titanium **Finish:** Cromo **Code:** 18D307081
Location: Baño **Category:** Ducha

Technical characteristics

- Ceramic cartridge Ø35 mm.
- Water saving system S2 through the handle opening in two fases.
- Flow rate at 3 bar (43 PSI): 12 l/min through hand shower outlet and 16 l/min through showerhead outlet.
- Thermal shock resistant and anti-Legionella chemical.
- Guarantee of 5 year for tapware and 3 years for accesories.
- Use pressure between 1-5 bar (14.5-72.5 PSI). Recomend pressure 3 bar (43 PSI).
- Resists static pressure equal to or less than 10 bar (145 PSI) and water hammer up to 25 bar.
- 3 bar (43 PSI) acoustic level less than 20 dB.
- Comfort benefits of fidelity, sensibility and constancy in temperature selection.
- Recomend temperature for hot water: 55°C. Maximum temperature of use: 65°C up to 1 hour at 90°C.
- Termostop Black system for maximum water temperature limitation.

Tests

- Water tightness, flow rate, mechanical behavior under pressure, mechanical resistance, dimensional, acoustical and corrosion test according to european standards EN 817 and EN 248.

Composition and spare parts

- Handle: 1800-35 (252987)
- Flow limiter: LC1212 (AAZ310503)
- Cartridge: 35100-3 (AAZ300855)
- Cartridge nut cover: 4980 (252834)
- Cartridge nut: TSC350 (253014)
- Diverter valve: IDH1/2 (300096)
- Seat: AGM-2I (252816)
- Index: DT1-CN (252825)
- Escutcheon + Eccentric: 1324 (182094)
- Escutcheon: 1325 (167127)
- Eccentric: E1/23/4 (160248)
- Hand shower: 2876BT (261595)
- Screw seat: T3/4 (160220)
- Shower support: SD25 (AAZ306948)
- Wall bracket: SFT25L34 (AAZ307403)
- Tube fixing bracket: SFDN132D (AAZ307406)
- Shower flexible hose: 1125C (99Z302692)
- Shower head: RP240 (251322)
- Shower column: DN132 (AAZ307070)

