



Sink mixer single lever with swivel spout and a 3rd way for filtered water, chromed

7589

Collection:
Kitchen

Finish:
Chrome

Code:
255336

Location:
Kitchen

Category:
Kitchen sink

Technical characteristics

- Ceramic cartridge Ø35 mm.
- Flow rate at 3 bar: 12 l/min.
- Thermal shock resistant and anti-Legionella chemical.
- Guarantee of 5 year for tapware and 3 years for accessories.
- Use pressure between 1-5 bar. Recommended pressure 3 bar.
- Resists static pressure equal to or less than 10 bar and water hammer up to 25 bar.
- 3 bar acoustic level less than 20 dB.
- Comfort benefits of fidelity, sensibility and constancy in temperature selection.
- Recommended temperature of use from 15°C to 55°C. Maximum use temperature 65°C. Maximum 1h at 90°C
- Chromed surface: 15 microns thick of nickel and 0.3 microns thick of chrome.

Tests

- Water tightness, flow rate, mechanical behavior under pressure, mechanical resistance, dimensional, acoustical and corrosion test according to european standards EN 817 and EN 248.

Composition and spare parts

- Fitting: RM01P (AAZ311376)
- Osmosis aerator: 1617 (AAZ306467)
- Handle: 7500IFV-35 (300230)
- Index: DT1-CN (252825)
- Cartridge nut cover: 4980 (252834)
- Cartridge nut: TSC351 (250863)
- Cartridge: 35000 (300224)
- Joint kit: BJC7589 (AAZ310205)
- Spout: C7589 (AAZ311374)
- Headwork: 7591 (AAZ302090)
- Flexible hose spout: 240 (AAZ302035)
- Handle wheel: 7500-01 (75Z311372)
- Aerator: 1589 (241106)
- Base: 753002 (75Z311373)
- Fixation bag: BS7589 (AAZ311375)
- Flexible hose: 237 (AAZ300858)

