



898801MC CHROME SINK CYLINDRICAL SPOUT FLEXIBLE WITH OSMOSIS

898801MC

Collection:
Kitchen

Finish:
Chrome

Code:
38E306084

Location:
Kitchen

Category:
Kitchen sink

Technical characteristics

- Ceramic cartridge Ø25 mm.
- Flow rate at 3 bar: 8 l/min
- Thermal shock resistant and anti-Legionella chemical.
- Guarantee of 5 year for tapware and 3 years for accesories.
- Use pressure between 1-5 bar. Recomend pressure 3 bar.
- Resists static pressure equal to or less than 10 bar and water hammer up to 25 bar.
- 3 bar acoustic level less than 20 dB.
- Comfort benefits of fidelity, sensibility and constancy in temperature selection.
- Recommended temperature of use from 15°C to 55°C. Maximum use temperature 65°C. Maximum 1h at 90°C
- Chromed surface: 15 microns thick of nickel and 0.3 microns thick of chrome.

Tests

- Water tightness, flow rate, mechanical behavior under pressure, mechanical resistance, dimensional, acoustical and corrosion test according to european standards EN 817 and EN 248.

Composition and spare parts

- Osmosis aerator: 1563 (AAZ301775)
- Handle: 380001-25 (38Z308054)
- Index: DT5-GN (AAZ308598)
- Cartridge nut cover: 4970 (252843)
- Cartridge nut: TSC256 (AAZ306246)
- Cartridge: 25000-2 (214341)
- Hand shower: DC3888 (AAZ303942)
- Support arm: BSC8988 (AAZ310946)
- Headwork: 8991 (AAZ306305)
- Wing nut: TP3/8X2 (AAZ305358)
- Handle wheel: 899001 (38Z308732)
- Aerator: 1599 (AAZ303269)
- Base: 383001 (38Z305715)
- Reinforcement base: BRF02 (AAZ304483)
- Accesory bag: BAC38 (AAZ303940)
- Felxible hose: 239 (AAZ301713)
- Threaded tube: CRF320 (AAZ304358)
- Flexible hose outlet: 268 (AAZ310486)
- Flexible connection red: 239R (AAZ301712)

Observations

- Filtered water flow rate at 3 bar: 2,2 l/min

