



## Shattaf set for WC cistern and trigger spray, chromed 113502

<b>Collection:</b> Wc	<b>Finish:</b> Cromo	<b>Code:</b> 99F301566
<b>Location:</b> Baño	<b>Category:</b> Wc	

### Technical characteristics

- Thermal shock resistant and anti-Legionella chemical.
- Guarantee of 5 year for tapware and 3 years for accesories.
- Use pressure between 1-5 bar (14.5-72.5 PSI). Recomend pressure 3 bar (43 PSI).
- 3 bar (43 PSI) acoustic level less than 20 dB.
- Recommended temperature of use from 15°C to 55°C. Maximum use temperature 65°C. Maximum 1h at 90°C
- Chromed surface: 15 microns thick of nickel and 0.3 microns thick of chrome.

### Tests

- Water tightness, flow rate, mechanical behavior under pressure, mechanical resistance and corrosion test according to european standards EN 1113 and EN 248.

### Composition and spare parts

- |                         |                     |
|-------------------------|---------------------|
| • Hand shower:          | 955102 (99Z304035)  |
| • Shower flexible hose: | 247903C (99Z307905) |
| • Shower support:       | 354802 (99Z302082)  |
| • Standard angle valve: | 3793 (99Z303339)    |

