



WC Magnet by Ramon Soler, concealed single lever for WC with shattaf set, chromed

336801WC

Collection:
Wc

Finish:
Chrome

Code:
99F302081

Location:
Bath

Category:
Wc

Technical characteristics

- Ceramic cartridge $\varnothing 25$ mm.
- Flow rate at 3 bar: 8 l/min.
- Thermal shock resistant and anti-Legionella chemical.
- Guarantee of 5 year for tapware and 3 years for accessories.
- Use pressure between 1-5 bar. Recommended pressure 3 bar.
- Resists static pressure equal to or less than 10 bar and water hammer up to 25 bar.
- 3 bar acoustic level less than 20 dB.
- Comfort benefits of fidelity, sensibility and constancy in temperature selection.
- Recommended temperature of use from 15°C to 55°C. Maximum use temperature 65°C. Maximum 1h at 90°C
- Chromed surface: 15 microns thick of nickel and 0.3 microns thick of chrome.

Tests

- Water tightness, flow rate, mechanical behavior under pressure, mechanical resistance, dimensional, acoustical and corrosion test according to european standards EN 817 and EN 248.

Composition and spare parts

- Hand shower: 9552 (230037)
- Shower flexible hose: 247903C (99Z307905)
- Handle: 3300-25 (33Z302683)
- Wall plate: FXX6801 (AAZ302656)
- Cartridge: 25000-2 (214341)
- Cartridge nut cover: 4970 (252843)
- Shower connector: RD11M (AAZ302655)
- Shirt concealed: CEMP3201 (AAZ306323)
- Cartridge nut: TSC256 (AAZ306246)
- Index: DT3-CN (253032)

